

Government of **Western Australia** Department of **Communities**

Department of Communities

Modifications to Construction Specification

NATSPEC | BCA Class 1a and 10 buildings Single and grouped dwellings.

January 2025

The modifications contained within this document are to replace, remove or amend the relevant specification requirements.

This document records and supersedes those items listed in the Specification as detailed in the tables below.



Page No.	Relevant section	Modification	Reason
18 to 21	0250 Landscape - gardening	Remove worksection.	Specification update to align with landscape design guide and brief.
18	0251 Landscape - soils	Add worksection. Refer to appended landscape worksections document.	Specification update to align with landscape design guide and brief.
18	0252 Landscape - natural grass surfaces	Add worksection. Refer to appended landscape worksections document.	Specification update to align with landscape design guide and brief.
18	0253 Landscape - planting	Add worksection. Refer to appended landscape worksections document.	Specification update to align with landscape design guide and brief.
18	0254 Irrigation	Add worksection. Refer to appended landscape worksections document.	Specification update to align with landscape design guide and brief.
18	0255 Landscape - plant procurement	Add worksection. Refer to appended landscape worksections document.	Specification update to align with landscape design guide and brief.
18	0256 Landscape - establishment	Add worksection. Refer to appended landscape worksections document.	Specification update to align with landscape design guide and brief.
18	0257 Landscape - verges and street trees	Add worksection. Refer to appended landscape worksections document.	Specification update to align with landscape design guide and brief.

46	0451 Windows and glazed doors <u>2 PRODUCTS</u> 2.2 COMPONENTS Insect screens	 Replace the following paragraph: Requirement: Provide insect mesh screens fitted to operable windows and sliding doors. With the following paragraph: Requirement: Provide insect mesh screens to all operable windows that cannot be accessed without the use of a ladder. 	To align with Schedule of Inclusions - Class 1 and 2 Developments - Revision 2024
47	0451 Windows and glazed doors <u>2 PRODUCTS</u> 2.2 COMPONENTS Security screens	Add the following paragraph: Requirement: Provide security barrier screens to sliding doors, and operable and accessible windows.	To align with Schedule of Inclusions - Class 1 and 2 Developments - Revision 2024
50	0455 Door hardware <u>1 PRODUCTS</u> 1.1 COMPONENTS Door buffers and stops	Remove the following subclause: Door buffers and stops Internal doors: Floor or wall mounted door buffers or stops.	To align with Schedule of Inclusions - Class 1 and 2 Developments - Revision 2024
51	0455 Door hardware 2 EXECUTION 2.1 INSTALLATION Door buffers and stops	 Replace the following subclause: Door buffers and stops Fixing: Fix on the floor or wall, as appropriate, to prevent the door or door furniture striking the wall or other surfaces. With the following subclause: Door buffers Fixing: Screw fix door buffers to the floor or skirting, as appropriate, to prevent the door or door furniture striking the wall or other surfaces. 	To align with Schedule of Inclusions - Class 1 and 2 Developments - Revision 2024

56	0511 Lining <u>1 PRODUCTS</u> 1.1 MATERIALS AND COMPONENTS Access panels	Add the following subclause: Access panels Internal ceilings, except garages: Provide insulated access panels.	To align with Schedule of Inclusions - Class 1 and 2 Developments - Revision 2024
58	0551 Joinery <u>1 PRODUCTS</u> 1.1 JOINERY MATERIALS AND COMPONENTS Splashbacks	Remove the following paragraph: Glass: 6 mm toughened colourback safety glass to AS/NZS 2208 (1996).	To align with Schedule of Inclusions - Class 1 and 2 Developments - Revision 2024
60	0572 Miscellaneous fixtures and appliances <u>1 PRODUCTS</u> 1.2 APPLIANCES Cooking appliances	 Replace the following paragraph: Cooktop: Provide one of the following: Gas cooktop: Where reticulated gas is available, provide minimum 4 burners, stainless steel, gas cooktop. Electric cooktop: Where reticulated gas is not available, provide minimum 4 zone, ceramic glass, electric cooktop. With the following paragraph: Cooktop: Minimum 4 zone electric cooktop. 	To align with Schedule of Inclusions - Class 1 and 2 Developments - Revision 2024
61	0574 Window coverings <u>2 PRODUCTS</u> 2.3 COVERING TYPES Holland blinds	 Replace the following paragraph: Requirement: Complete proprietary systems, as documented, fabricated by one manufacturer. With the following paragraph: Requirement: Vertical blinds provided as complete proprietary systems fabricated by one manufacturer. Do not provide horizontal blinds. 	To align with Schedule of Inclusions - Class 1 and 2 Developments - Revision 2024

70	0651 Resilient finishes	Replace the following paragraph:	To align with Schedule of
	2 PRODUCTS	Total thickness: Minimum 4 mm.	Inclusions - Class 1 and 2
	2.1 MATERIALS	With the following paragraph:	Developments - Revision 2024
	Vinyl planks	Total thickness: Minimum 2 mm.	
70	0651 Resilient finishes	Add the following paragraph:	To align with Schedule of
	2 PRODUCTS	Warranty: Minimum 15 years.	Inclusions - Class 1 and 2
	2.1 MATERIALS		Developments - Revision 2024
	Vinyl planks		
70	0651 Resilient finishes	Add the following subclause:	To align with Schedule of
	3 EXECUTION	General	Inclusions - Class 1 and 2
	3.2 INSTALLATION	Requirement: Install to the manufacturer's recommendations.	Developments - Revision 2024
	General		
78	0802 Hydraulic	Add the following paragraph:	To align with Schedule of
	2 PRODUCTS	Hanging space: Minimum 1200 mm.	Inclusions - Class 1 and 2 Developments - Revision 2024
	2.2 FIXTURES		Developments - Revision 2024
	Towel rails		
78	0802 Hydraulic	Replace the following paragraph:	Specification update requested
	2 PRODUCTS	Type: Provide one of the following:	by Construction on 09.09.2024 (removal of lockable laundry
	2.2 FIXTURES	- Tub and cabinet with lockable side entry for concealed washing machine	cabinets)
	Laundry tub and cabinet	taps. - Tub integrated with joinery.	
		With the following paragraph:	
		Type: Provide one of the following:	

78	0802 Hydraulic <u>2 PRODUCTS</u> 2.2 FIXTURES	 42 L tub and prefinished steel cabinet with side entry for concealed washing machine taps. Tub integrated with joinery. <i>Replace the following paragraph:</i> Type: All fittings other than bath outlets and showers to be chrome plated lever handled mixer tap (hot and cold) with 150 mm swivel arm with aerator outlet. <i>With the following paragraph:</i>	To align with Schedule of Inclusions - Class 1 and 2 Developments - Revision 2024
	Internal tap fittings	Type: Chrome-plated lever handled mixer tap (hot and cold) with 150 mm swivel arm with aerator outlet.	
78	0802 Hydraulic	Remove the following paragraph:	To align with Schedule of
	2 PRODUCTS	Gas hot water heaters: To AS/NZS 5263.1.2 (2020). If a flue damper is available	Inclusions - Class 1 and 2 Developments - Revision 2024
	2.3 WATER HEATERS	for the water heater supplied, provide one.	
	Types	- Energy performance: To AS/NZS 4552.2 (2010).	
79	0802 Hydraulic	Remove the following paragraph:	To align with Schedule of
	3 EXECUTION	5-star natural gas hot water units: Connect hot water service to points as	Inclusions - Class 1 and 2 Developments - Revision 2024
	3.3 COLD AND HEATED	documented.	
	WATER	- Hot water system: Design and install to AS/NZS 3500.4 (2021).	
	Water heaters		
83	0902 Electrical	Add the following clause:	To align with Schedule of
	3 EXECUTION	2.3 CEILING FANS - GENERALLY	Inclusions - Class 1 and 2 Developments - Revision 2024
	2.3 CEILING FANS -	General	
	GENERALLY	Controls: Hardwired adjustable speed control switch. Do not provide remotes.	
	General		

84	0902 Electrical	Replace the following paragraph:	To align with Schedule of
	3 EXECUTION	Luminaire type: Provide the following, as documented:	Inclusions - Class 1 and 2
	3.4 LIGHTING Luminaire	 Oyster light fittings: 32W, 350 mm diameter (nominal) fluorescent fittings and acrylic diffuser. LED recessed downlights: Insulation contact (IC) rated 15W fittings spaced at maximum 1.5 m spacing. Fluorescent tube fittings: Twin 18W T8 fluorescent tube, battens and clear prismatic diffuser or vandal resistant cover. 	Developments - Revision 2024
		With the following paragraph:	
		Luminaire type: Provide the following, as documented:	
		 Oyster light fittings: 32W, 350 mm diameter (nominal) LED fittings and acrylic diffuser. LED recessed downlights: Insulation contact (IC) rated 15W fittings spaced at maximum 1.5 m spacing. LED tube fittings: Twin 18W T8 LED tube, battens and clear prismatic diffuser or vandal resistant cover. 	3
84	0902 Electrical	Add the following paragraph:	To align with Schedule of
	3 EXECUTION	Communal areas: Provide LED lighting as follows:	Inclusions - Class 1 and 2 Developments - Revision 2024
	3.4 LIGHTING	- Type: One of the following:	
	Luminaire	 Wall mounted. Ceiling mounted. In-ground fixed bollard. Light pole style. Solar powered. Vandal resistant with tamper proof fixings. Minimum IP rating: IP68. 360-degree lighting output. Warranty: Minimum 10 years. 	

85		Replace the following paragraph:	To align with Schedule of Inclusions - Class 1 and 2
	3 EXECUTION 3.5 TELECOMMUNICATIONS	Data cabling: Conform to the requirements of the NBN company. With the following paragraph:	Developments - Revision 2024
	Services and cabling	Data cabling: Conform to the requirements of the utility service provider.	
85	0902 Electrical	Add the following paragraph:	To align with Schedule of
	<u>3 EXECUTION</u>	NBN installation: Conform to the NBN Guideline (2024), including the following:	Inclusions - Class 1 and 2 Developments - Revision 2024
	3.5 TELECOMMUNICATIONS	- New buildings: To the <i>NBN Guideline (2024)</i> Section 3.	
	Services and cabling	- Location type: Open enclosures to the <i>NBN Guideline (2024)</i> clause 7.2.	
85	0902 Electrical	Remove the following subclause:	To align with Schedule of
	3 EXECUTION	NBN installation	Inclusions - Class 1 and 2 Developments - Revision 2024
	3.5 TELECOMMUNICATIONS	Requirement: To the NBN Guideline (2021).	
	NBN installation	New buildings: To the NBN Guideline (2021) clause 3.6.	
		Location type: Open enclosures to the NBN Guideline (2021) clause 4.4.3.	